

**EXPANDED METAL PATTERNS SPANMESH™**

**SpanMesh™ Security Table**

					% OPEN AREA	WEIGHT/# SQ. FT.
PATTERN	MATERIAL GAUGE	SWD	LWD	FLAT/RAISED	RANGE MIN. - MAX.	RANGE MAX. - MIN.
1/2"-#18	18	.500	1.200	FLAT/RAISED	25-82	1.38 - .33
1/2"-#16	16	.500	1.200	FLAT/RAISED	25-76	1.84 - .59
1/2"-#14	14	.500	1.200	FLAT/RAISED	25-70	2.30 - .92
1/2"-#13	13	.500	1.200	FLAT/RAISED	25-64	2.82 - 1.32
* 1/2"-#13	13	.500	1.200	RAISED	57	1.47
* 1/2"-#13	13	.500	1.200	RAISED	25	2.82
5/8"-#18	18	.625	1.200	FLAT/RAISED	25-86	1.38 - .26
5/8"-#16	16	.625	1.200	FLAT/RAISED	25-81	1.84 - .47
5/8"-#14	14	.625	1.200	FLAT/RAISED	25-76	2.30 - .74
5/8"-#13	13	.625	1.200	FLAT/RAISED	25-71	2.76 - 1.06
3/4"-#16	16	.923	2.000	FLAT/RAISED	25-87	1.84 - .32
3/4"-#14	14	.923	2.000	FLAT/RAISED	25-84	2.30 - .50
3/4"-#13	13	.923	2.000	FLAT/RAISED	25-80	2.75 - .72
3/4"-#9	10	.923	2.000	FLAT/RAISED	25-73	3.83 - 1.38
* 3/4"-#9	10	.923	2.000	RAISED	68	1.80
* 3/4"-#9	10	.923	2.100	FLATTENED	63	1.71
1 1/2"-#16	16	1.330	3.000	FLAT/RAISED	25-90	1.84 - .22
1 1/2"-#14	14	1.330	3.000	FLAT/RAISED	25-89	2.30 - .35
1 1/2"-#13	13	1.330	3.000	FLAT/RAISED	25-86	2.76 - .50
1 1/2"-#9	10	1.330	3.000	FLAT/RAISED	25-81	3.84 - .96
2"-#14	14	1.850	4.000	FLAT/RAISED	25-92	2.30 - .24

\* Per ASTM F 2548-06 Standard specification for expanded metal fence systems for security purposes