

<b>STYLE</b>	<b>STEEL (GA.)</b>	<b>STAINLESS (GA.)</b>	<b>ALUM (IN.)</b>	<b>SWD RANGE</b>	<b>LWD RANGE</b>	<b>MAX. WIDTH (LWDB)</b>
MINI MESH	18 - 30	20 - 30	.010" - .050"	.070" - .150"	.105" - .180"	40"
SMALL MESH	18 - 30	20 - 30	.010" - .080"	.150" - .250"	.250" - .516"	72"
MEDIUM MESH	16 - 30	18 - 30	.010" - .100"	.300" - .400"	.600" - .700"	62"
LARGE MESH	16 - 30	18 - 30	.010" - .100"	.375" - .400"	.800	70"
SMALL DIAMOND	14 - 22	16 - 22	.025" - .090"	.250" - .400"	.600" - 1.000"	62"
MEDIUM DIAMOND	13 - 22	14 - 22	.025" - .125"	.500" - .750"	1.000" - 1.500"	72"
LARGE DIAMOND	6 - 20	12 - 20	.050" - .190"	.750" - 1.250"	2.000" - 2.750"	72"
EXTRA LARGE DIAMOND	6 - 20	10 - 20	.050" - .190"	1.500" - 2.000"	3.000" - 4.000"	72"
* ALL STYLES CAN BE PROVIDED IN FLATTENED, SEMI-CROWNED, OR STANDARD UNFLAT						
* STRAND WIDTH CAN RANGE APPROXIMATELY BETWEEN ONE TO TWO TIMES RAW MATERIAL THICKNESS						
* FLATTENED THICKNESS IS TYPICALLY 10 TO 20 PERCENT BELOW RAW MATERIAL THICKNESS						
* PERCENT OPEN AREA CAN VARY APPROXIMATELY BETWEEN 20 TO 90 PERCENT OPEN DEPENDING ON PATTERN						
* THE ABOVE STYLES ARE ALSO AVAILABLE IN SPECIALTY METALS						